

AMENDMENTS TO THE CLAIMS:

1. (Previously presented) A three-dimensional camera based position determination system, comprising:

an optically scannable target device fixedly attached to a target object;

at least one camera and light subsystem, each subsystem having:

an image sensing device configured to view the optically scannable target device and to generate image information indicative of geometric characteristics of the target device; and

at least one invisible light emitting diode operatively coupled to a strobe circuit, the at least one diode and circuit being configured to emit strobed invisible light thereby illuminating the optically scannable target such that the light is retro-reflected to the image sensing device and the image sensing device detects and forms an image of the target;

a data processing device operatively coupled to the image sensing device, the data processing device being configured to determine the orientation of the target object based on the generated target image; and

a visible indicator that indicates whether the at least one invisible light emitting diode is operative.

2. (Original) The position determination system as recited in Claim 1, wherein the invisible light is infrared light.

3. (Previously presented) The position determination system as recited in Claim 2, wherein the visible indicator emits light within the visible spectrum, and thereby indicates that the at least one invisible light emitting diode is operative.

4. (Original) The position determination system as recited in Claim 1, wherein the at least one invisible light emitting diode is an array of light emitting diodes.

5. (Original) The position determination system as recited in Claim 4, wherein the number of invisible light emitting diodes in the array is sixty-four.

6. (Original) The position determination system as recited in Claim 4, wherein the number of invisible light emitting diodes in the array is eighty.

7. (Original) The position determination system as recited in Claim 1 wherein the target object is a vehicle wheel, and the data processing device is further configured to determine proper wheel alignment based on orientation of the vehicle wheel.

8. (Original) The position determination system as recited in Claim 3, wherein the image sensing device includes an electronic shutter that is synchronized with the at least one strobed light emitting diode such that an image is captured only when a target is illuminated.

9. (Original) The position determination system as recited in Claim 8, wherein the image sensing device is a charge-coupled device video camera.

10. (Original) The position determination system as recited in Claim 8, wherein the image sensing device is a complimentary metal oxide semiconductor camera.

11. (Cancelled)

12. (Original) The position determination system as recited in Claim 1, further comprising:

a current source configured to supply a current to the at least one invisible light emitting diode.

13. (Currently Amended) A three-dimensional camera based position determination system, comprising:

an optically scannable target device fixedly attached to a target object;

at least one camera and light subsystem, each subsystem having:

an image sensing device configured to view the optically scannable target device and to generate image information indicative of geometric characteristics of the target device; and

at least one light emitting diode operatively coupled to a strobe circuit, the at least one diode and circuit being configured to emit strobed light thereby illuminating the optically scannable target such that the light is retro-reflected to the image sensing device and the image sensing device detects and forms an image of the target;

a data processing device operatively coupled to the image sensing device, the data processing device being configured to determine the orientation of the target object based on the generated target image; and

a target object indicator, disposed on the camera and light subsystem, configured to display that displays the status of target acquisition by the data processing device, wherein the status of target acquisition indicates whether an obtained image of the scannable target device is acceptable

14. (Currently Amended) The position determination system as recited in Claim 13 wherein the target object indicator is configured to provide an indication for each target object to indicate whether the obtained image of each respective target object is acceptable. ~~comprises:~~

~~—— a target object indicator array that includes at least one set of target object indicator light emitting diodes, wherein each light emitting diode of the first set corresponds to a target object;~~

~~—— wherein the target object indicator array further includes a second set of target object indicator light emitting diodes, wherein each light emitting diode of the second set corresponds to a target object; and~~

~~—— wherein the target object indicator array is operatively coupled to the data processing device such that the first set of target object light emitting diodes is energized when an image of the target object is acquired by the data processing device, thereby indicating that the target object is acquired by the data processing device, and the second set of target object light emitting diodes is energized when an image of the target object is not acquired by the data processing device, thereby indicating that the target object is not acquired by the data processing device.~~

15. (Currently Amended) The position determination system as recited in Claim 13, further comprising:

~~at least two sets of directional light arrays, each of the sets of directional light arrays including at least one directional light emitting diode, and wherein, the at least two sets of directional light arrays are operatively coupled to the image sensing device such that when a single set of directional light is energized, a directional indicator for indicating a direction manner by which the target object should be manipulated is indicated in which the target object should be repositioned such that the image sensing device may sense the target object and wherein, when all directional light arrays are on, the target object has been properly positioned.~~

16. (Currently Amended) The position determination system as recited in Claim 15, wherein: ~~the number of directional light arrays is four, and the directions~~

the target object is a vehicle; and

the directional indicator indicates whether in which the vehicle should be repositioned as indicated by the four arrays are backward, forward, moved forward or backward, or whether a wheel of the vehicle should be steered right or left and right.

17. (Previously presented) A three-dimensional camera based position determination system, comprising:

sensing means for sensing an image of a target device, and generating image information indicative of geometric characteristics of the target device; and

emission means for emitting strobed invisible light that illuminates the optically scannable target such that the light is retro-reflected to the image sensing device and the image sensing device detects and forms an image of the target;

data processing means for determining the orientation of the target object based on the generated target image; and

visible indicator means for visibly indicating whether the emission means is operative.

18. (Original) The position determination system as recited in Claim 17, wherein the invisible light is infrared light.

19. (Previously presented) The position determination system as recited in Claim 18, wherein the visible indicator means emits light within the visible spectrum, and thereby indicates that the emission means is operative.

20. (Original) The position determination system as recited in Claim 17, wherein the target object is a vehicle wheel, and the data processing means is configured to determine proper wheel alignment based on orientation of the vehicle wheel.

21. (Original) The position determination system as recited in Claim 17, wherein the image sensing means includes an electronic shutter that is synchronized with the emission means such that an image is captured only when a target is illuminated.

22. (Original) The position determination system as recited in Claim 17, further comprising:

attachment means for fixedly attaching an optically scannable target device to a target object.

23. (Original) The position determination system as recited in Claim 17, further comprising:

directional means for indicating the direction in which a target object should be repositioned, and for indicating that a target object has been properly positioned.

24. (Original) The position determination system as recited in Claim 17, further comprising:

target object indicator means for indicating that the sensing means is sensing the target object.

25. (Original) The position determination system as recited in Claim 17, further comprising:

target object indicator means for indicating the state of target acquisition by the data processing device.

26. (Currently Amended) An image-based position determination system for optically scanning a target device related to an object, the system comprising:

at least one camera and light subsystem, each subsystem having:

an image sensing device configured to view the target device and to generate image information indicative of geometric characteristics of the target device;

at least one light emitting diode operatively coupled to a strobe circuit, the at least one diode and circuit being configured to emit strobed light thereby illuminating the target device such that the light is retro-reflected to the image sensing device and the image sensing device detects and forms an image of the target; and

a visual indicator for indicating a manner by which the object should be manipulated such that the image sensing device obtains an image of the target device in a different position-direction by which the object should be moved relative to the image sensing device;

and

a data processing device configured to couple to the visual indicator and the image sensing device to determine the orientation of the object based on the generated target image.

27. (Currently Amended) An image-based position determination system for optically scanning a target device related to an object, the system comprising:

image sensing means for viewing the target device and for generating image information indicative of geometric characteristics of the target device;

light emitting means for emitting strobed light thereby illuminating the target device such that the light is retro-reflected to the image sensing means and the image sensing means detects and forms an image of the target; and

visual indicator means for indicating a ~~direction by which the object should be moved~~
~~relative to the image sensing means~~manner by which the object should be manipulated such that
the image sensing means obtains an image of the target device in a different position;

and

a data processing device configured to couple to the visual indicator means and the image
sensing means to determine the orientation of the object based on the generated target image.

28. (Currently Amended) A three-dimensional camera based position determination
system, comprising:

an optically scannable target device fixedly attached to a target object;

at least one camera and light subsystem, each subsystem having:

an image sensing device configured to view the optically scannable target device
and to generate image information indicative of geometric characteristics of the target
device; and

at least one light emitting diode operatively coupled to a strobe circuit, the at least
one diode and circuit being configured to emit strobed light thereby illuminating the
optically scannable target such that the light is retro-reflected to the image sensing device
and the image sensing device detects and forms an image of the target;

a data processing device operatively coupled to the image sensing device, the data
processing device being configured to determine the orientation of the target object based on the
generated target image;

a target object indicator that displays the status of target acquisition by the data processing device, wherein the status of target acquisition indicates whether an obtained image of the scannable target device is acceptable, and~~The system of Claim 13 further comprising:~~

directional means for indicating the direction in which the target object should be repositioned, and for indicating whether the target object has been properly positioned.